# Sana MOTORIZATION


fashion forward



### Sahara Motorization Collection

### 1 1/8" MOTORIZED H-RAIL SETS





### SAHARA MOTORIZATION COLLECTION

1 1/8" MOTORIZED SETS



**AVAILABLE FINISHES** XX = finish color





All Forest Shuttle motors include a 10-year warranty.

### MOTOR OPTIONS



52925-25 Shuttle HD (M) white 52925-59 Shuttle HD (M) black



**52923-25** Shuttle L



**52939-25** Shuttle Eco (S)



**52926-25** Shuttle iOn

### **FINIAL OPTIONS**

ALL SAHARA 1 1/8" COLLECTION FINIALS CAN BE USED ON SAHARA MOTORIZATION RODS. REFER TO THE SAHARA COLLECTION CATALOG FOR FINIAL OPTIONS.

### ASSEMBLED RODS AVAILABLE THROUGH **CDH STOCKING DISTRIBUTORS**

ASSEMBLED ROD SETS INCLUDE RAIL. SINGLE WALL BRACKETS, MOTOR, POWER SUPPLY, AND DIAMOND WALL SWITCH OR REMOTE.



#### 1 1/8" SAHARA MOTORIZATION COMPONENTS



Sahara Motorizable Rod WIM-144-PW 12' Pewter WIM-235-CH 19' 7" Chrome WIM-132-CH 11' 7" Chrome WIM-096-CH 8' Chrome WIM-235-BL 19' 7" Black WIM-142-BL 11' 7" Black WIM-096-BL 8' Black



Sahara Extended Cylinder Bracket



B11682-XX Recess Bracket with Return Pulley



B11679-L-XX Left Motor Pulley B11679-R-XX Right Motor Pulley



B11683-L-XX Left Return Pulley B11683-R-XX Right Return Pulley




WI-16B5-XX



WI-16C2-XX Ceiling Bracket



WI-16C1-XX Flush Ceiling Bracket Cannot use finials



WI-16SP2-01 Rail Connector



52008-XX -25 white, -59 black Slim Line Contract Klick Shape helps pleats hang straight box of 250



Carrier w/ Square Base in plastic sleeve. Use 4 1/4" snap tape. roll of 500


Two-Piece Connected Snap 2114-25 60% fullness, 2 5/8" OC 2111-25 80% fullness, 2 3/8" OC -59 black, -90 silver 2112-25 100% fullness, 2 1/8" OC 2115-25 120% fullness, 1 7/8" OC



52009-25 **Ball Bearing Carrier** for motorization box of 100



52508-XX Overlap R 52509-XX Underlap L -25 white, -59 black Belt Master Carrier box of 100



52508-XXA Overlap R 52509-XXA Underlap L -25 white, -59 black Belt Master Carrier w/ snaps box of 100



**52409-25** Butt L **52410-25** Butt R Standard Butt Master w/ snaps




2552-25 6' Extension Arm for master Use w/ 2 one-way draws box of 50



Shuttle Motor Power Supply 52928-25 7' 6" power cord **52934-25** 16' power cord



9012-25 Transport Belt, Kevlar reinforced 328 feet/roll



52512-25 Transport Belt Connector, connects belt to master box of 100



**52931-25D** white **52931-59D** black Diamond Sensor Remote w/ holder Range 98' RF, 15 channel



52933-25 white 52933-59 black Diamond Wall Switch 2 channel



52947-25 Wireless Connector One-way transmitter to control drapery by third party app or home automation. Works with all Forest Shuttle motors. Includes smart plug.






52948-25 white **52948-59** black Wi-Fi Dongle Bi-directional communication using the Forest Connect app. Works with all Forest Shuttle motors.



# Sahara MOTORIZATION 1 1/8" collection



n	DIMENS
Ź	MAXIMU
2	TRAVEL
<b>8</b>	RECEIVE
Ť	AMPER A

### DIMENSIONS

**JM WEIGHT** 

SPEED

٩GE

TORQUE

**NOISE LEVEL** 

**COLOR OPTIONS** 

WI-FI COMPATIBLE

PLUG & PLAY WARRANTY

TOUCH CONTROL TECHNOLOGY INTEGRATED EMERGENCY CONTROL RF COMMUNICATION STANDARD **Z-WAVE COMMUNICATION AUTOMATION SYSTEM COMPATIBLE** 

WORKS WITH DS-XL LED DIMMER

WORKS WITH WIRELESS CONNECTOR CAN BE USED WITH CURVED TRACK

10 Years

2.76" x 1.97" x 9.5"

160 lbs per motor

100 lbs per motor			
5.5" per second standard 7" per second maximum			
Internal			
.8 amps / 40 watts 110 volt plug-n-play			
1.0 Nm			
< 40 dB(A)			
White			
$\sqrt{}$			
√ √ √			
$\sqrt{}$			
$\sqrt{}$			
√ using RS485 & dry contacts			

2.76" x 1.97" x 11"	2.76" x 1.97" x 7.5"
100 lbs per motor	100 lbs per motor
5.5" per second standard 7" per second maximum	5.5" per second standard 7" per second maximum
Internal	Internal
.8 amps / 40 watts 110 volt plug-n-play	.35 amps / 40 watts 110 volt plug-n-play
1.0 Nm	1.0 Nm
< 40 dB(A)	< 40 dB(A)
White	White
$\sqrt{}$	$\sqrt{}$
$\sqrt{}$	$\sqrt{}$
$\sqrt{}$	$\sqrt{}$
$\sqrt{}$	-
$\sqrt{\text{using RS485 \& dry contacts}}$	$\sqrt{\text{using RS485 \& dry contacts}}$
$\sqrt{}$	$\sqrt{}$
√ (requires separate power adaptor)	$\sqrt{}$

10 Years



## Sahara MOTORIZATION 1 1/8" collection



### **SHUTTLE iOn**



### **DIMENSIONS**

MAXIMUM WEIGHT

TRAVEL SPEED

RECEIVER

**SPECIFICATIONS** 

AMPERAGE

TORQUE

**NOISE LEVEL** 

**COLOR OPTIONS** 

TOUCH CONTROL TECHNOLOGY INTEGRATED EMERGENCY CONTROL RF COMMUNICATION STANDARD **Z-WAVE COMMUNICATION AUTOMATION SYSTEM COMPATIBLE** 

WI-FI COMPATIBLE

WORKS WITH DS-XL LED DIMMER

WORKS WITH WIRELESS CONNECTOR

CAN BE USED WITH CURVED TRACK

PLUG & PLAY

WARRANTY

### 2" x 3" x 12.25"

55 lbs per motor

5.5" per second standard

### Internal

Lithium Ion Battery + charger (3-4 months between charges)

1.0 Nm

<40 dB(A)

White

√ using RS485 & dry contacts

10 Years on motor 2 years on battery pack

### **CONTROL OPTIONS**

Our wide range of control options make finding a fit for your home easy. Control the drapes by hand, remote, or even by the home automation system. Controlling the motorized system with your smart phone or tablet, you can create and schedule customized room scenes that allow your drapes to operate on their own throughout the day no matter where you are.



#### **FOREST DIAMOND SENSE** REMOTE

15-channel remote controls up to 15 motors individually and together,

with a timer or manually. Range up to 98 feet. Wall mounted holder included.



### **FOREST WI-FI DONGLE**

With the Forest Wi-Fi Dongle, you can control your motorized system with your smart phone or tablet using the Forest Connect app, or by voice command when integrated with Google Home, Amazon Echo and Siri.



### **FOREST WIRELESS** CONNECTOR

With the Wireless Connector make your new or existing Shuttle motorized drapery system "smart". Add a smart plug and use with Apple HomeKit, Google Assistant, or Amazon Alexa. Also, easily incorporate with building management systems, including dry contact controls.



### **BUILDING AUTOMATION /** HOTEL ROOM CONTROLS

Forest Shuttles M, L & S can be connected to any building automation system, by relay



